

S	Model	EXZ51K
1	Engine Model	6WF1-TCC
2	Driving System	6X4
3	Engine Type	4 Cycle,Direct injection,water cooled,in-line,OHC intercooled turbo charger
4	No of Cylinders	6
5	Bore x Stroke	147x140
6	Displacment cc	14256
7	Max Output HP / rpm	390 /1800
8	Max Torque(kg.m) / rpm	190 /1100 (kg.m)
9	Compration Ratio	17
10	Clutch Type	Hydraulic control with air assisted
11	Clutch Size mm	390 mm, Dry twin plate with angle spring
12	Transmission Type	MJXP16P
13	Gear Diameter mm	445
14	Gear Ratio	5.125
15	Brake Service	Full-air, dual circuit taper roller type,leading-trailing on front & rear wheels plus ABS
16	Brake Auxiliary	Exhaust brake electro-pnumatic control with butterfly valve in exhaust pipe
17	Brake Parking	Spring Actuate at front and rear wheels, control valve on the floor
18	Steering	Recirculating ball nut type with integral power assisted
19	Axle Front	Reverse elliot, I beam Capacity 7500kg
20	Axle Rear	Banjo, fully floating,tandem drive,hypoid gear with inter-axle differential & locking device capacity 26 ton
21	Suspention,Front	Semi-elliptical alloy steel long leaf spring, shackle type
22	Suspention,Rear	Semi-elliptical alloy steel leaf spring,trunnion suspension type
23	Frame Type	Ladder type channel section with high tensile steel
24	Frame Size	285x85x7
25	Disc Wheel& Tire size	825X22.5 ,295/80R-22.5
26	Battery	115F51
27	Starter V	24V-7KW
28	Fuel Tank Lit	550
29	Cab Type	Tilt cabin, Monocoque consitruction with bed space & 3-seat
30	Head Lamp	Bumper integrated
31	Windshield	Laminated glass
32	GCM (Kg)	60000
33	GVM	26000(tractor only)
34	Mass Kg	8670-8710
35	WB	4685
36	OAL	6746
37	FOH	1400
38	ROH	661
39	CE	4690
40	OW	2490
41	OH	3030
42	Accessories	AM/FM radio with CD player,Sunvisor,Cup holder,AC Manual Control,tool Box kit(empty),Jack 10 Ton ,2 Mirror outside,Tire inflator device,Tachometer